

# DRYING CABINET

DC  
RANGE

DC 8 HP

8KG  
17LB



## FEATURES

- Heat pump drying cabinet
- Very low energy consumption, only 0,28 kWh/kg
- Capacity 8 kg
- Hanging length 16 m
- Four automatic programs dry the clothes until they are dry, not a minute longer thanks to the Humidity Tracking System (HTS)
- One programme for time drying
- The doors open 190°
- Hanging rail rotates 180° to the outside
- Lighting inserted
- The feet are adjustable from the inside of the cabinet
- Delivered semi-mounted, top packed as an assembling kit
- Language options: English, French, German, Swedish, Norwegian, Danish and Spanish instructions
- CE approved

## OPTIONS

- Hook rack, set of three
- Hanginf rails

## MARKETS

Laundries, Laboratory, Fire brigades, Police stations, Army, Airports, Campings, Golf clubs, Football clubs, Diving schools, Theatres, Spas, Horse farms, Oil platforms, Ski resorts, Fish industries, Marines, Ships

MAIN SPECIFICATIONS		DC8 HP
Loading capacity	kg/lbs	up to 8 /17,6
Drying capacity	g/min	45*
Hanging length	m/feet	16
Drying time	min	58*
Total power	kW	1,5
Energy consumption /kg	kWh	0,28

\* Drying of 6 kg cotton (dry weight), washed and high-spinned to 43% residual moisture, dried to 0 % residual moisture.

TECHNICAL SPECIFICATIONS		DC8 HP
<b>ELECTRICAL CONNECTIONS</b>		
Standard electrical connection		380-415V/50/60Hz/3phase + N
Fuse	A	10
Total power	kW	1,5
Drain pipe	Ø mm/inch	12/0,47
Cooling liquid		R407C
Pressure drop	max Pa	70
<b>SOUND LEVEL</b>		
Airborne sound level	dB(A)	56
<b>SHIPPING DATA</b>		
Net	kg/lbs	165/364
Crated	kg/lbs	15/33,1
Shipping data net	kg/lbs	180/397
Shipping volume	m <sup>3</sup>	1,6
<b>OPTIONAL ACCESSORIES</b>		
Hook rack, set of three	part number	POD131071
<b>DIMENSIONS</b>		
Width	mm/inch	1200/47,2
Depth	mm/inch	650/25,6
Height	mm/inch	1995/78,5

