



HIGH-SPIN HYGIENIC BARRIER WASHER-EXTRACTORS

IB900	IB1100	IB1400	IB1800
90KG	110KG	140KG	180KG

FEATURES

- Freestanding, high spin
- Stainless steel cabinet
- Stainless steel drum and tub
- MICRO - new graphic display with almost unlimited possibilities as:
 - communication interface enabling remote service
 - multilingual microprocessor
 - freely programmable
- Oversized frame, bearings and drum
- Large door opening for easy loading and unloading
- Large drain valve (Ø 126 mm)
- Easy access to all parts
- Frequency controlled motor
- Perforated lifting ribs: more mechanical action, lower water consumption
- Standard Y-pocket (3 pockets) drum on IB1100, IB1400, IB1800
- Standard Pullman (2 pockets) drum on IB900
- Eco-friendly washing programs - significantly reduces water and electricity consumption
- Soap dispenser with 5 removable compartments (10 compartments on IB1800)
- Automatic door positioning



OPTIONS

- Liquid soap pumps
- Drum with 2 pockets on IB1100, with 3 pockets on IB900
- Water sample tap
- Light and sound signalisation of end of washer cycle
- Second display
- Horizontal door



HYGIENIC
SOLUTION



LARGE DOOR
OPENING



STAINLESS
STEEL IDENTITY

	IB900	IB1100	IB1400	IB1800
DRUM				
CAPACITY 1:10 (KG)	90	110	140	180
CAPACITY 1:9 (KG)	100	122	155,5	200
VOLUME (L)	900	1100	1400	1800
DRUM DIAMETER (MM)	1000	1100	1200	1300
POCKETS	standard 2 optional 3	standard 2 optional 3	standard 3	standard 3
MOTOR				
FREQUENCY CONTROLLED	standard	standard	standard	standard
DRUM SPEED				
WASH SPEED (RPM)	36	35	33	36
EXTRACTION SPEED (RPM)	800	754	720	695
G-FACTOR	360	350	350	350
HEATING				
ELECTRICAL ADDITIONAL HEATING (KW)	54	72	72/96	-
STEAM HEATING (BAR)	6-8	6-8	6-8	6-8
CONNECTIONS				
ELECTRICAL	3 x 380-480V/50-60Hz 3 x 200-240V/50-60Hz	3 x 380-480V/50-60Hz 3 x 200-240V/50-60Hz	3 x 380-480V/50-60Hz 3 x 200-240V/50-60Hz	3 x 380-480V/50-60Hz 3 x 200-240V/50-60Hz
WATER INLET (MM)	3 x 1,5" + 1 x 3/4"	3 x 1,5" + 1 x 3/4"	3 x 1,5" + 1 x 3/4"	3 x 1,5" + 1 x 1"
STEAM INLET (MM)	1"	1"	1"	1"
COMPRESSED AIR INLET (MM)	Ø10	Ø10	Ø10	Ø10
DRAIN DIAMETER (MM)	Ø126	Ø126	Ø126	Ø126
TRANSPORT DATA				
GROSS WEIGHT (KG)	2970	3150	3760	5310
NET WEIGHT (KG)	2810	2990	3550	4990
DIMENSIONS H x W x D (MM)	1805 x 2275 x 1615	1855 x 2325 x 1615	2075 x 2435 x 1805	2165 x 2585 x 1905
PACKING DIMENSIONS H x W x D (MM)	1985 x 2355 x 1740	1986 x 2400 x 1740	2250 x 2485 x 1940	2265 x 2665 x 2040
VOLUME (M ³)	8,1	8,7	10,8	12,3

* Tested in accordance of EN604-56 norm.
The data concerning dimensions of machines include all extended parts.

