



INDUSTRIAL TUMBLE-DRYER

IDR195

9 KG

FEATURES

- Standard stainless steel drum
- Anthracite grey skin plate
- Black top panel
- Easy-to-use microprocessor (ECT)
- Innovative bulged drum
- Axial airflow
- 210° door opening for easy loading and unloading
- Intuitive control with simple selection and 3 programs

OPTIONS

- Stainless steel front
- Reverse drum
- Residual moisture control
 - safe drying of delicate linen
 - humidity detection in %
- Heating power from 6 (kW) up to 12 (kW), to match various installation requirements
- Coin operated version



LOW ENERGY
CONSUMPTION

YOUR SMART LAUNDRY PARTNER



INDUSTRIAL TUMBLE-DRYER

IDR195 HP

9 KG

FEATURES

- Standard stainless steel drum
- Anthracite grey skin plate
- Inox top panel
- Easy-to-use microprocessor (ECT)
- Innovative bulged drum
- Axial airflow
- 210° door opening for easy loading and unloading
- Intuitive control with simple selection and 3 programs
- Triple filtration system
- Optimized 0.65m2 footprint to install anywhere

OPTIONS

- Stainless steel front
- Reverse drum
- Coin operated version



LOW ENERGY
CONSUMPTION



HEAT PUMP

YOUR SMART LAUNDRY PARTNER

	IDR195	IDR195 HP
DRUM		
CAPACITY	9	
VOLUME (L)	195	
DIAMETER (MM)	670	
DEPTH (MM)	555	
DOOR		
DOOR OPENING (MM)	Ø 500	
OPENING	Right (reversible)	
DOOR OPENING ANGLE (°)	210	
DRYING PERFORMANCE		
AIRFLOW TYPE	axial	
AIRFLOW (M ³ /H)	300	-
HEATING		
HEATING TYPE	Electric	Heat pump
HEATING POWER (kW)	6 / 9 / 12	1,5
TOTAL POWER SUPPLY (kW)	6,4 / 9,4 / 12,4	2
ELECTRICAL CONNECTION	3 x 220-230V - 50Hz 3 x 220-230V - 60Hz 3 x 240V - 50Hz 3 x 380-415V + N - 50 Hz 3 x 380-415V + N - 60 Hz 3 x 380-415V - 50 Hz 3 x 380-415V - 60 Hz 3 x 440 V - 60 Hz	3 x 220-240V - 50Hz 3 x 380-415V+N - 50Hz
MOTOR		
FAN (KW)	0,25	0,17
DRIVE (KW)	0,25	0,25
CONNECTION		
EXHAUST (MM)	150	N/A
WATER VALVE CONNECTION (IN)	N/A	2 x 1"
CONDENSATE DRAIN (MM)	N/A	16
PROGRAMMER		
PROGRAMMER	Easy Control	
NOISE LEVEL		
DRYING SEQUENCE (dB)	55	54
DIMENSIONS		
H X W X D (MM)	1150 x 710 x 945	1725 x 710 x 925
NET WEIGHT (KG)	125	193
TRANSPORT DATA		
PACKED H X W X D (MM)	1253 x 752 x 970	1815 x 752 x 970
GROSS WEIGHT (FOIL) (KG)	135	208