



# INDUSTRIAL TUMBLE-DRYER

**IDR250**

12 KG

**IDR285**

16 KG

**IDR345**

19 KG

## FEATURES

- Standard galvanized drum with large diameter
- Easy-to-use microprocessor (ECT)
- Combination of radial and axial airflow
  - maximal heat transfer
  - low energy consumption
  - short drying time
- Large door opening for easy loading and unloading
- Self cleaning lint screen

## OPTIONS

- Coin operated version
- Stainless steel drum
- Reverse drum
- Double door glass and insulation
- Flex Control Programmer (FCT)
- Residual moisture control
  - safe drying of delicate linen
  - humidity detection in %
  - ideal in combination with Softwash®
  - Ideal for dry cleaners, fire departments
  - available on Easy and Flex Control
- Stainless steel front
- Wireless communication with cloud-based systems (WiFi kit - to order through Accessories)



	IDR250	IDR285	IDR345
DRUM			
CAPACITY 1:18 (KG)	12	16	19
CAPACITY 1:22 (KG)	11	13	16
VOLUME (L)	250	285	345
DIAMETER (MM)	Ø760		Ø760
NUMBER OF DRUMS	1		1
NUMBER OF LOADING DOORS	1		1
DRYING PERFORMANCE			
AIRFLOW (M <sup>3</sup> /H)	520	550	600
DRYING AVERAGE (L/MIN)	0,166 (EL) / 0,187 (G)	0,206 (EL) / 0,223 (G)	0,260 (EL) / 0,270 (G)
GAS HEATING			
GAS CONNECTION (IN)	1/2"		1/2"
ELECTRICAL CONNECTION - gas heating	1x 208-240V 50Hz, 3x 208-240V 50Hz, 3x 380-415V +N 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 50Hz, 3x 480V 60Hz		
GAS OUTPUT (KW)	16,5	19,5	25
ELECTRICAL HEATING			
ELECTRICAL CONNECTION - electric heating	3x 208-240V 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 60Hz		
ENERGY (kW)	13,5	<b>13,5</b> / 18,0	<b>18,0</b> / 24,0
STEAM HEATING			
STEAM CONNECTION (NPT)	3/4"	3/4"	3/4"
ELECTRICAL CONNECTION- steam heating	3x220-240V 50Hz, 1x220-240V 50Hz, 3x380-415V 50Hz	1x 208-240V 50Hz, 3x 208-240V 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 50Hz, 3x 480V 60Hz	
STEAM OUTPUT * (kW)	16,6 - 19,4 / 20,0 - 23,3	25,5 - 29,9 / 21,5 - 24,0	25,5 - 35,6 / 24,8 - 27,7
STEAM PRESSURE (BAR)	3-6/7-10	3-6/7-10	3-6/7-10
MOTOR			
FAN (KW)	0,55	0,55	0,55
DRIVE (KW)	0,25	0,25	0,25
PROGRAMMER			
EASY CONTROL- antivandal (ECT)	Standard	Standard	Standard
FLEX CONTROL	Available	Available	Available
DIMENSIONS			
H X W X D (MM)	1680 x 795 x 1070	1680 x 795 x 1160	1680 x 795 x 1280
NET WEIGHT (KG)	230	230	240
TRANSPORT DATA			
PACKED H X W X D (MM)	1785 x 855 x 1100	1785 x 855 x 1190	1785 x 855 x 1310
GROSS WEIGHT (KG)	245	250	260

\* Steam output is flexible depending on steam pressure, The data concerning dimensions of machines include all extended parts

