



# INDUSTRIAL TUMBLE DRYERS WITH HEAT PUMP

IHP250 | IHP285 | IHP345  
11 KG | 13 KG | 16 KG

## FEATURES

- Heat pump
- Standard galvanized drum with large diameter
- Easy to use microprocessor (Easy)
- Combination of radial and axial airflow concept:
  - Maximal heat transfer
  - Low energy consumption
- Large drain valve (Ø 76 mm)
- Large door opening for easy loading & unloading
- Self cleaning lint screen

## OPTIONS

- Stainless steel side front
- Stainless steel drum
- Reversing drum
- Full control programmer (Flex)
- Residual moisture control
  - Safe drying of delicate linen
  - Humidity detection in %
  - Ideal in combination with wet cleaning
  - Ideal for dry cleaners, fire departments
  - Available on Easy and Flex Control
- Coin operated version
- Wireless communication with cloud-based systems (WiFi kit - to order through Accessories)



HEAT PUMP



ENERGY  
EFFICIENT

	IHP250	IHP285	IHP345
INNERDRUM			
CAPACITY 1:18 (KG)	12	16	19
CAPACITY 1:22 (KG)	11	13	16
VOLUME (L)	250	285	345
DIAMETER (MM)	760	760	760
DRYING AVERAGE (G/MIN)	118	130	130
MOTORS			
FAN (KW)	0,30	0,30	0,30
DRIVE (KW)	0,25	0,25	0,25
HEAT PUMP			
ELECTRICAL CONNECTION	3 x 208-240V 50HZ / 3x380-415V 50Hz +N / 3 x 440V 60Hz		
ENERGY (KW)	2,9	2,9	2,9
PROGRAMMER			
EASY CONTROL	standard	standard	standard
FLEX CONTROL	available	available	available
TRANSPORT DATA			
DIMENSIONS H X W X D (MM)	1680 x 795 x 1525	1680 x 795 x 1615	1680 x 795 x 1735
GROSS WEIGHT (KG)	385	400	400
NET WEIGHT (KG)	350	360	375

Energy consumption comparison  
CONVENTIONAL DRYER vs. HEAT PUMP DRYER

