

HIGH SPIN SOFTMOUNT WASHER-EXTRACTORS

IY800 | IY1000 | IY1200

FEATURES

- Freestanding, high spin
- Stainless steel cabinet
- Stainless steel drum and tub
- Aries Elite Fully programmable microprocessor
- Extra large door opening (IY800, IY1000 Ø530mm, IY120 Ø650mm)
- Two large drain valves (Ø103mm)
- · Easy access to all parts
- · Standard liquid soap connections
- · Frequency controlled motor
- · Patended soap dispenser with 5 removable compartments
- Perforated lifting ribs: more mechanical action, lower water consumption
- Air operated water inlet
- Eco washing programs significantly reduces water and electricy consumption

OPTIONS

- · Liquid soap pumps
- · Aries Assist
- · Forward and backward tilting is available. Tilting of the machine is done by external platform.





ROBUST DESIGN





EASY OPERATION

	IY800	IY1000	IY1200
INNERDRUM			
CAPACITY 1:10 (KG)	80	100	120
CAPACITY 1:9 (KG)	89	111	133
VOLUME (L)	807	972	1154
DIAMETER (MM)	1110	1200	1300
DRUM SPEED			
WASH (RPM)	36	33	32
EXTRACTION (RPM)	750	720	695
G-FACTOR	350	350	350
HEATING			
ELECTRICITY (KW)	67,5	-	-
STEAM HIGH PRESSURE (BAR)	3-8	3-8	3-8
STEAM HIGH PRESSURE (PSI)	44-116	44-116	44-116
CONNECTIONS			
ELECTRICAL	3 x 200-240/50-60 Hz 3 x 380-480/50-60Hz	3 x 200-240/50-60 Hz 3 x 380-480/50-60Hz	3 x 200-240/50-60 Hz 3 x 380-480/50-60Hz
MOTOR (KW)	11	15	18,50
WATER INLET (MM)	3 x 38 (1 1/2")	3 x 38 (1 1/2")	3 x 38 (1 1/2")
STEAM INLET (MM)	25 (1")	25 (1")	25 (1")
COMPRESSED AIR INLET (MM)	Ø8	Ø8	Ø8
DRAIN (MM)	2 x 103 (4")	2 x 103 (4")	2 x 103 (4")
TRANSPORT DATA			
GROSS WEIGHT (KG)	2830	3410	3710
NET WEIGHT (KG)	2640	3170	3480
DIMENSIONS H x W x D (MM)	1985 x 1495 x 1940	2060 x 1790 x 2005	2085 x 1855 x 2085
PACKING DIMENSIONS H x W x D (MM)	2200 x 1690 x 1950	2345 x 1865 x 2125	2340 x 2000 x 2170
VOLUME (PACKED) (M³)	7,25	9,29	10,16

- = not available Standard = standard execution. The data concerning dimensions of machines include all extended parts

