



starLine 7720

- Load capacity: 7 kg
- Large 4.3" colour display
- Drum vanes for 3D-Washing
- LED drum lighting
- Drum capacity: 60l
- Spin speed: 1500 rpm
- g Factor 605
- Residual moisture 44%
- With drain valve or drain pump
- Language selection button
- profiClean programme button
- 35 profiClean and 24 freely programmable slots
- Powder-coated steel housing, matt grey
- Door hinge right or left
- Available in anthracite



starLine TC 7730

- Load capacity: 7 kg
- Large 4.3" colour display
- Stainless steel drum
- LED drum lighting
- Condensation system
- Drum capacity: 118l
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Powder-coated steel housing, matt grey
- Door hinge right or left
- Available in anthracite

Company or brand name		Schulthess	
Type of appliance		Washing machine	
Type or sales description		starLine 7720	
Product number		7720.2	
Application features			
Load capacity	max. kg	7	
Drum capacity	l	60	
Spinning speed	max. rpm	1500	
g Factor	g	605	
Residual moisture ¹⁾	%	44	
Structural design			
Footed appliance with work surface		•	
Door hinge ³⁾		r / l / w	
Dimensions			
Height	cm	85	
Width	cm	60	
Depth including distance from wall	cm	67	
Depth with door open (front loader)	cm	110	
Height (adjustable)	cm	1	
Weight when empty	kg	90	
Equipment			
Detergent tank and drum		chrome-nickel steel	
Loading opening		Ø cm 34 / 180°	
Automatic door opening		•	
Connecting cable		m 1,6	
Drain:			
– Drain hose with benda, only model (P)		m	1,5
– Model with drain pump (P)		Ø mm	21
– Model with drain valve (V)		Ø mm	50
Electric power and water supply			
Electrical connection		400 V 2N~ / 50Hz / 4,6kW / 10A	
Voltage / connected loads / fuse		230 V 1N~ / 50Hz / 2,3kW / 10A	
Water connection			
– Pressure hose G ¾" with fine filter		m	1,5
– Can be connected to cold water / hot water		cold water / hot water 70 °C	
– Water pressure		bar	1–10
Options			
– Door hinge left			
– Hot water connection			
– Drain valve or drain pump			
– Connection for 8 liquid detergents with dosing pump			
– Machine plinth			
– Machine plinth with drawer for fluff filter			
Safety and service			
Conforms to the European Machinery Directive		2006/42/EC	
Country of origin		Switzerland	
Guarantee		1 year	
Service by		Schulthess Maschinen AG	
Name and address of supplier		Schulthess Maschinen AG, CH-6330 Cham ZG	

Explanations:

– Available or yes • Not available or no

1) Values determined in the 60°C cotton programme.

3) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

7) Information on switchover options can be found in the installation instructions, where required.

Note: State of the table details as 03.2021, subject to further developments.

Company or brand name		Schulthess	
Type of appliance		Condensation dryer	
Type or sales description		starLine TC 7730	
Product number		7730.2	
Load capacity	max. kg	7	
Structural form			
Footed appliance with work surface		•	
Standard unit for wash and dry column		•	
Door hinge ³⁾		r / l / w	
Dimensions ⁴⁾			
Height	cm	85	
Width	cm	60	
Depth including space from wall	cm	64	
Height for built-in installation	cm	85,5	
Depth with door open	cm	122	
Height adjustable	cm	2	
Drying control			
By time selection ⁵⁾		•	
Automatic by electronic moisture detection ⁶⁾		•	
System and equipment			
Drying technology		Air condensation system	
Programme time display		•	
Load quantity display		•	
Automatic door opening		•	
Loading opening		cm	orne, Ø 36 / 31 / 180°
LED drum lighting		•	
Connecting cable		m	1,5
Outlet hose		m	2 / Ø 22 mm
Condensate drainage in container / Drainage direct		•	
Exhaust line		–	
Maximum drainage height		m	1
Exhaust hose Ø 100 mm		m	–
Power supply			
Electrical connection ⁷⁾			
Voltage		V	400 V 2N~ / 230 V 1N~
Connected values		kW	2,8 / 2,1
Fuse protection		AT	10 / 10
Safety and service			
Conforms to the European Machinery Directive		2006/42/EC	
Country of origin		Switzerland	
Guarantee		1 year	
Service by		Schulthess Maschinen AG	
Name and address of supplier		Schulthess Maschinen AG, CH-6330 Cham ZG	

Explanations:

– Available or yes • Not available or no

3) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

4) The stated dimensions are minimum dimensions for the niche where the machine is built in. Further dimensions can be found in the dimension sheets.

5) Set the degree of drying according to the laundry items, as shown in the operating instructions.

6) Degree of drying is maintained automatically.

7) Information on switchover options can be found in the installation instructions, where required.