

STACK TUMBLE DRYERS

DX
RANGE

DX13/13 **DX20/20**

2X13KG
2X30LB

2X20KG
2X45LB



FEATURES

- ☒ Double capacity on the same footprint
- ☒ Controls:
 - Dual Digital Control or OPL Micro
 - Coin operated version: XQ-Control
- ☒ Gas or Electrical heating (DX13/13)
- ☒ Large door opening for easy loading and unloading (DX 13/13 Ø 57cm, DX 20/20 Ø 68cm)
- ☒ Galvanized drum
- ☒ Axial airflow
- ☒ Large lint filter

OPTIONS

- ☒ Stainless steel drum
- ☒ Stainless steel front panel with black painted door
- ☒ Coin operated version
- ☒ Residual moisture control Sensodry+® (only with Full OPL Micro):
 - lower energy and utility costs
 - lower linen replacement costs
- ☒ SafeTech™ Fire Suppression System
- ☒ Reversing drum



SUITABLE FOR
LAUNDROMATS



STACKABLE
UNIT



EASY
OPERATION

TYPE		DX13/13	DX20/20
CAPACITY			
Capacity	kg	2x13	2x20
Drum volume	l	2x300	2x420
Drum diameter	mm	Ø 762	Ø 838
AIRFLOW			
Airflow	l/s	380	570
DRYING AVERAGE			
Gas heating	g/min	294	385
Electric heating	g/min	258	-
MOTOR			
Fan	kW	2x0,4	2x0,4
Drive	kW	2x0,2	2x0,4
GAS HEATING			
Energy (per pocket)	kW	21,4	27,8
Energy (per pocket)	kBTU/h	73	95
Electrical connection		1x100-120V/50-60Hz, 1-3x200-240V/50-60 Hz 3x440-480V/50-60Hz, 3x380-415V/50-60Hz	
Gas connection (one manifold)	NPT	½"	½"
ELECTRICAL HEATING			
Energy (per pocket)	kW	21	-
Electrical connection		3x200-208V/50-60Hz, 3x230-240V/50-60Hz 3x380V/50-60Hz, 3x400-415V/50-60Hz 3x440V/50-60Hz, 3x460-480V/50-60Hz	
EXHAUST	Ø /mm	1x200	1x250
DIMENSIONS			
Size HxWxD	mm	1940x800x1090	2065x875x1235
Net weight (E, G, S)	kg	300, 260, 275	-, 320, -
TRANSPORT DATA			
Packed (foil) HxWxD	mm	2030x830x1190	2160x900x1370
Gross weight (foil E, G, S)	kg	300, 270, 290	-, 340, -
Packed (crate) HxWxD	mm	2210x900x1270	2210x1020x1520
Gross weight (crate E, G, S)	kg	360, 330, 350	-, 420, -

Side DX 13/13 20/20

Back DX 13/13 20/20

